



## KNITTED COPPER TUBULAR BRAID

1/1

06/07

# F 4

### 1 - CONSTRUCTION

- Hollow Knitted tubular braid with red tinned copper yarn.
- Flat presentation.



### 2 - CHARACTERISTICS

REFERENCE	WIDTH mm	WEIGHT g/m	THICKNESS mm	YARN DIAMETER mm	STICHES cm	Number of assembled yarns	Number of Needles
CU 05	25	10.5	0.50	12	4.5	1	38
CU 07	50	15.5	0.50	12	2.5	1	54
CU 25	60	26.0	0.50	12	2.8	2	44
CU 26	52	69.0	1.00	15	2.5	5	26
CU 27	50	24.0	0.50	12	4.5	1 et 2	54
CU 29	50	17.0	0.50	12	5.0	1	54
CU 30	60	14.0	0.60	15	2.5	1	26
CU 03	80	47.5	0.90	25	2.0	1	30
CU 28	50	54.0	0.70	15	2.2	4	26

### 3 - APPLICATIONS

- Earthing in cables junctions.
- Repairing kits ( or junctions ) for energy transport cables.

### 4 - PRESENTATION

- Presentation :  
on neutral ring, central axis 40 mm.  
without ring.  
with or without stopping by needle.
- Conditioning: with or without individual film.
- Length per roll:  
for ex : CU 05 = 4,6ml - 10ml  
CU 26 = 6ml - CU 29 = 5m  
Other lengths : please question us.

