

**1 - CONSTRUCTION**

- Round and hollow glass fiber E braid with tight stitches.
- Slightly impregnated with epoxy resin and heat treated in order to :  
Partially eliminate impregnation and block the sleeving in order to flexible and resistant to crushing and fraying.



**2 - CHARACTERISTICS**

SPECIFICATION	UNIT	1 CT	2 CT	3 CT
Number of braids		1	2	3
Temperature Resistance	°C	350	350	350
Dry Dielectric Strength	Volt	≥ 500	≥ 1500	≥ 2000
Incombustible		Yes	Yes	Yes
Resistance to fraying		Good	Very good	Very good

**3 - APPLICATIONS**

- Ovens, furnaces, heating appliances, electric dryers.
- Domestic appliances, soldering irons, heating resistance.
- Various cables. Good mechanical resistance.

**4 - PRESENTATION**

- Conditioning : on cardboard jaws bobbins.
- Colour : brown.
- Diameters :  
1 CT : 1-1,5-2-2,5-3-3,5-4-4,5-5-6-7-8-9-10-12mm  
2 CT : 1,5-2-2,5-3-3,5-4-5-6-8mm  
3 CT : 2,5-3-4-5-8mm  
Other diameters, please question us.



We recommend to protect them from heat, humidity and at an ambient temperature.