

1 - CONSTRUCTION

- Made of :
 - BRAID = Discontinuous or continuous glass yarn interlaced in layers.
 - CORE = Discontinuous or continuous glass yarn (Verranne).
- UNBLEACHED (Textile ensimage). This is the standard quality.
- The fire loss is practically 0%, the cord is incombustible.

- The cords are BRAIDED and get the reference :
 - "V" with the discontinuous glass yarn.
 - "SV" with the discontinuous and continuous glass yarn.


2 - CHARACTERISTICS

DIAMETER mm	REFERENCE	WEIGHT g/m average \pm 10 %
5 x 5	05 x 05	30
6 x 6	06 x 06	43
8 x 8	08 x 08	60
10 x 10	10 x 10	80
12 x 12	12 x 12	120
14 x 14	14 x 14	150
16 x 16	16 x 16	180
18 x 18	18 x 18	210
20 x 20	20 x 20	215
25 x 25	25 x 25	290
30 x 30	30 x 30	460
35 x 35	35 x 35	850
40 x 40	40 x 40	1000
45 x 45	45 x 45	1220
50 x 50	50 x 50	1350
HEAT TEMPERATURE : 450 to 500 °C		



3 - APPLICATIONS

- Thermic seals. Ovens, Boilers.
- Insulation.
- bindings.
- Reinforcement for collector.

4- PRESENTATION

DIAMETER mm	REFERENCE	LENGTH PER BOBBIN m
5 x 5	05 x 05	100
6 x 6	06 x 06	100
8 x 8	08 x 08	100
10 x 10	10 x 10	50
12 x 12	12 x 12	50
14 x 14	14 x 14	50
16 x 16	16 x 16	50
18 x 18	18 x 18	50
20 x 20	20 x 20	30
25 x 25	25 x 25	20
30 x 30	30 x 30	20
35 x 35	35 x 35	20
40 x 40	40 x 40	10
45 x 45	45 x 45	10
50 x 50	50 x 50	10

Colour UNBLEACHED - On request : black tinted

