

1 - CONSTRUCTION

- Glass cloth support.
- Thermosetting adhesive mass.



2 - CHARACTERISTICS

SPECIFICATION	UNIT		R 14	R 142	R 143
Thermal Class			B - 130°C	F - 155°C	H - 180°C
Nature of support			Glass	Glass	Glass
Adhesive Mass			Rubber	Acrylic	Silicone
Total Thickness	mm		0.16	0.18	0.17
Breaking Resistance	N/cm		280	280	280
Dielectric strenght	Volt		1500	2000	2300
Temperature Resistance	°C		130	155	180
Adhesive Strenght of Steel	N/cm		4	2.5	3.5
Insulating resistance	MΩ		1.5 x10 ³	1.5 x 10 ³	1.5 x 10 ³
Breaking Elongation	%		8	8	8
Corrosion factor			0.95	0.95	0.95
Lifetime	Month		6	6	6
Reticulation time		2 hours at 130°C - 1 hour at 150°C			

3 - APPLICATIONS

- Banding of bobbins.External finishing of bobbins.
- Wrapping of cables.insulation of inductor bobbins.
- Repairing of motors. Protection anti-vibratory.
- Insulation between layers, between phases, of external yarns.

4 - PRESENTATION

- Standard widths :
9 - 12- 15 - 19 - 25 - 30 - 38 - 50 - mm.
other widths : please question us.
- Colours : white .
- Meters per roll :
33M on 76mm cores for the ref. R143.
50M on 76mm cores for the ref. R14 - R141 -R142.



We recommend to protect the tape from heat, humi-dity and at a temperature between + 10 and + 30°C.