

1 - CONSTRUCTION

- Plastified P.V.C support, self-extinguishing.
- Good electrical properties, flexible and comfortable.



2 - CHARACTERISTICS

SPECIFICATION	UNIT	R 18	R 26
Nature of support		PVC	PVC
Adhesive Mass		Rubber	Rubber
Total Thickness	mm	0.18 +0.01 -0.02	0.14 +0.01 -0.02
Breaking Resistance	N/cm	≥ 35	≥ 22
Dielectric Strength	kV/mm	≥ 38	≥ 36
Temperature of use	°C	0 à + 90	0 à + 85
Adhesive Strength of Steel	N/cm	≥ 1.8	≥ 2.0
Breaking Elongation	%	≥180	≥ 150
Insulating Resistance	MΩ	10 ¹⁰	10 ⁷
Lifetime	Month	24	24

3 - APPLICATIONS

- Insulation of cables, electrical uses.
- Banding and repairing of cables in telecommunications.
- Industrial applications.



4 - PRESENTATION

- Standard widths:
19 - 25 mm.
other widths : please question us.
- Colour : black.
other colours : please question us.
- Meter per roll :
33M on 32mm cores.
20M on 32mm cores.



we recommend to protect the tape from heat, humidity and at a temperature between + 10 and + 25°C, box up, roll flat.