

### 1 - CONSTRUCTION

- Round and hollow glass fiber E braid with tight stitches.
- Slightly impregnated with epoxy resin and heat treated in order to :  
Partially eliminate impregnation and block the sleeving in order to flexible and resistant to crushing and fraying.



### 2 - CHARACTERISTICS

| SPECIFICATION           | UNIT | 1 CT  | 2 CT      | 3 CT      |
|-------------------------|------|-------|-----------|-----------|
| Number of braids        |      | 1     | 2         | 3         |
| Temperature Resistance  | °C   | 350   | 350       | 350       |
| Dry Dielectric Strength | Volt | ≥ 500 | ≥ 1500    | ≥ 2000    |
| Incombustible           |      | Yes   | Yes       | Yes       |
| Resistance to fraying   |      | Good  | Very good | Very good |

### 3 - APPLICATIONS

- Ovens, furnaces, heating appliances, electric dryers.
- Domestic appliances, soldering irons, heating resistance.
- Various cables. Good mechanical resistance.

### 4 - PRESENTATION

- Conditioning : on cardboard jaws bobbins.
- Colour : brown.
- Diameters :  
1 CT : 1-1,5-2-2,5-3-3,5-4-4,5-5-6-7-8-9-10-12mm  
2 CT : 1,5-2-2,5-3-3,5-4-5-6-8mm  
3 CT : 2,5-3-4-5-8mm  
Other diameters, please question us.



We recommend to protect them from heat, humidity and at an ambient temperature.