

1 - PROPERTIES

| | |
|---------------------|--|
| Material | Silicone |
| Shore Hardness | From 60 to 70 Sh A |
| Temperature of use | - 80 + 240 °C (Softness to be kept in low temperatures) |
| Chemical Properties | Good resistance to fluids (citric acid, alcohols, vegetal and animal oils) |
| Breaking Elongation | 300 % |
| Density | 1,20 g/cm ³ |
| Dielectric Strength | 20 KV/mm |
| Breaking Strength | 9,5 N/mm ² |

2 - CHARACTERISTICS

| DIAMETER | LENGTH | DIAMETER | LENGTH |
|----------|--------|----------|--------|
| 1 x 3 | 100 M | 10 x 14 | 50 M |
| 2 x 6 | 100 M | 12 x 16 | 50 M |
| 3 x 6 | 100 M | 16 x 22 | 50 M |
| 4 x 8 | 50 M | 18 x 22 | 50 M |
| 6 x 9 | 50 M | 22 x 29 | 50 M |
| 8 x 12 | 50 M | 30 x 35 | 50 M |
| | | | |

For other dimensions, please contact us

3 - APPLICATIONS

- Cabling - Mechanical and dielectric protection
- Motor industry - Electrical appliances - medical - food - electro technical industry.
- Good flexibility.

4 - PRESENTATION

- Coils : from 20 m to 100 m.
- Colours : Translucid (other colors are available).
- Diameters : Available from 1 to 35 mm.

