

### 1 - CONSTRUCTION

- Hollow Knitted tubular braid with red tinned copper yarn.
- Flat presentation.



### 2 - CHARACTERISTICS

| REFERENCE    | WIDTH<br>mm | WEIGHT<br>g/m | THICKNESS<br>mm | YARN DIAMETER<br>mm | STICHES<br>cm | Number of<br>assembled yarns | Number of<br>Needles |
|--------------|-------------|---------------|-----------------|---------------------|---------------|------------------------------|----------------------|
| <b>CU 05</b> | 25          | 10.5          | 0.50            | 0.12                | 4.5           | 1                            | 38                   |
| <b>CU 07</b> | 50          | 15.5          | 0.50            | 0.12                | 2.5           | 1                            | 54                   |
| <b>CU 25</b> | 60          | 26.0          | 0.50            | 0.12                | 2.8           | 2                            | 44                   |
| <b>CU 26</b> | 52          | 69.0          | 1.00            | 0.15                | 2.5           | 5                            | 26                   |
| <b>CU 27</b> | 50          | 24.0          | 0.50            | 0.12                | 4.5           | 1 et 2                       | 54                   |
| <b>CU 29</b> | 50          | 17.0          | 0.50            | 0.12                | 5.0           | 1                            | 54                   |
| <b>CU 30</b> | 60          | 14.0          | 0.60            | 0.15                | 2.5           | 1                            | 26                   |
| <b>CU 03</b> | 80          | 47.5          | 0.90            | 0.25                | 2.0           | 1                            | 30                   |
| <b>CU 28</b> | 50          | 54.0          | 0.70            | 0.15                | 2.2           | 4                            | 26                   |

### 3 - APPLICATIONS

- Earthing in cables junctions.
- Repairing kits ( or junctions ) for energy transport cables.

### 4 - PRESENTATION

- Presentation :  
on neutral ring, central axis 40 mm.  
without ring.  
with or without stopping by needle.
- Conditioning: with or without individual film.
- Length per roll:  
for ex : CU 05 = 4,6ml - 10ml  
CU 26 = 6ml - CU 29 = 5m  
Other lengths : please question us.

